

Shower toilet seat and cover, with lateral connections, with remote control 89189.1



TECHNICAL DATA

Order no.	89189.1
Certified to	CCE, IPX4, EN1717
Specifications	Duroplast, with antibacterial treatment, with lowering system with Quick release funktion for cleaning Remote control iOS and android app. connection
Water inlet	G 3/8" (male)
Working pressure	0.1 to 0.7 Mpa (1-7 bar)
Working temperature	+5 to +35 °C
Cleaning functions	Rear shower and lady shower 5 levels pressure adjustment 5 levels nozzle position adjustment 5 levels temperature adjustment Oscillating and pulsating cleaning mode
Dryer function	5 levels temperature adjustment
Seat heating	5 levels temperature adjustment
Comfort	Night light (bowl and ambience) Remote operation
Hygiene	Automatic self cleaning of nozzle and descaling process UV nozzle disinfection

Power supply & consumption	220-240V, 50/60Hz, plug type F Power saving mode Power cord length 1m
----------------------------	---

Weight	7,2 kg
Mounting acc. incl.	Remote control, order no. 89389.0 fastening kit Mounting instruction

Colours	000 – White
---------	-------------

SPECIFICATION TEXT

Shower toilet seat and cover, with remote control Laufen CLEANET SIT, Duroplast, with antibacterial treatment, with Quick release funktion for cleaning, seat with heating type

CCE, IPX4, EN1717, AC 220-240V, 50/60Hz, plug type F dimensions 370 x 490 x 85 mm

Special feature: remote control, rear shower and lady shower, with adjustable water pressure, temperature and nozzle position, oscillating and pulsating cleaning mode, automatic self cleaning nozzle and descaling process, UV nozzle disinfection, heated seat with adjustable temperature and soft closing lid and seat, integrated night light, power saving mode, iOS and android app. connection

Order no. 89189.1

TECHNICAL DRAWINGS / S 1 : 20

